Ref. : AM 300/308

PRODUCT SAFETY DATA SHEET

THIS DOCUMENT CONFORMS TO THE E.E.C. DIRECTIVE 91/155/CEE

PRODUCT NAME : Mitsubishi Motors Diamond Protect Reactive Polymer Paint Protection

1- COMPANY AND PRODUCT IDENTIFICATION

COMPANY NAME: Protection Brands
ADDRESS: Level 9, 3 Nexus Court, Mulgrave VIC 3107
PHONE: 1800 737 624

2- HAZARDS IDENTIFICATION

2.1 Non hazardous product in normal conditions of use.

3- COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 CHEMICAL NATURE : Water-in-oil emulsion.
3.2 SUBSTANCES : Hazardous ingredients : Less than 5% of nonionic surfactant ;5% and less than 15% of aminomethoxyfunctional polymers R36/38.
May be irritating to eyes and skin.
3.3 PREPARATION : Contains : 15% and less than 30% of aliphatic hydrocarbon
Cas No. 64742-48-9

4- FIRST AID MEASURES

GENERAL INFORMATION :
4.1 Ingestion : Do not induce vomiting, immediately call a physician and show him this sheet.
4.2 Eye contact : Immediately irrigate eye with clean water for 15 minutes and seek medical advice if irritation persists.
4.3 Skin contact : Wash off with soap and water.

5- FIRE FIGHTING MEASURES

5.1 Extinguishing media : Carbon dioxide, Foam, Dry chemical or fine spray water extinguisher.
5.2 Unusual fire and explosion hazards : None known.
5.3 Fire fighting equipment : Breathing apparatus.
5.4 Other recommendations : None.

Ref. : AM 300/308

PRODUCT SAFETY DATA SHEET

THIS DOCUMENT CONFORMS TO THE E.E.C. DIRECTIVE 91/155/CEE

PRODUCT NAME : Mitsubishi Motors Diamond Protect Reactive Polymer Paint Protection

6- ACCIDENTAL RELEASE MEASURES

6.1 Spillage actions : Soak up with sand and /or sawdust and dispose of in accordance with local regulations. Do not pour product in sewer, rivers, etc.

7- HANDLING AND STORAGE

7.1 Handling : Avoid contact with eyes and prolonged contact with skin.
7.2 Storage : Keep Product in its original container. Keep container closed when not in use.

8- EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Special protection : None required.

9- PHYSICAL AND CHEMICAL PROPERTIES

9.1 Appearance at 20 deg C : Liquid cream
9.2 Colour : White
9.3 Odour : Slight aliphatic hydrocarbon
9.4 P.H. : Not determined
9.5 Flash point : > 150 deg C
9.6 Freezing point : - < 0 deg C
9.7 Solubility in water : Slightly soluble in water.

10- STABILITY AND REACTIVITY

10.1 Materials to avoid : None known
10.2 Hazardous decomposition products : None known

11- TOXICOLOGICAL INFORMATION

11.1 Health hazards : May be irritating for skin and eyes after prolonged contact

12- ECOLOGICAL INFORMATION

12.1 Probable effect on the environment : Partially biodegradable. Nonionic surfactant over 90% biodegradable.

13- DISPOSAL CONSIDERATIONS

13.1 Can be incinerated in accordance with local regulations.

Ref. : AM 300/308

PRODUCT SAFETY DATA SHEET

THIS DOCUMENT CONFORMS TO THE E.E.C. DIRECTIVE 91/155/CEE

PRODUCT NAME :Mitsubishi Motors Diamond Protect Reactive Polymer Paint Protection

14- TRANSPORT INFORMATION

14.1 E.E.C. Regulations : Non – hazardous for transport in its original container.

ADR/RID

Hazard Class : Not Regulated

IMDG

Hazard Class : Not Regulated

ICAO/IATA

Hazard Class Not Regulated

15- REGULATORY INFORMATION

15.1 Limited exposure value on work sight : None known.

15.2 Labelling : No regulatory information required. Conforms to the EEC Directive 89/542/CEE dated September 13 1989 concerning labelling procedures for cleaning products.

16- OTHER INFORMATION

16.1 Recommended uses and restrictions : Treatment for painted surfaces and gel coat ready to use providing a brilliant shine with a hydrophobic protective film.

Whilst Protection Brands has taken every care to ensure accuracy of the data contained in this document, no guarantee or liability will be assumed. It is recommended that customers satisfy themselves of the suitability of all products purchased for their own use.